

## Counter-Balanced


Our standard selection of counter balanced flagpoles are available in mounted heights from 30 ft. to 50 ft. with a concrete foundation. For further assistance please refer to the Contact Us page for questions.

### Counter Balanced Standard Flagpoles, Tilting:


- Material:** Alloy 6063-T6 aluminum tubing with uniform conical taper. Counterweight box, base plate and support channels are made of steel
- Finish:** Directional sanded satin ground. Counterweight box matches color of pole
- Finial:** Gold anodized aluminum ball with flush seam
- Truck:** Single or double metal sheave cast aluminum with stainless steel bearing
- Halyard:** One or two #10 (5/16-dia.) braided polypropylene rope each with two chrome plated bronze swivel snap hooks
- Cleats:** One or two 9 inch cast aluminum, each attached with two 5/16-inch stainless steel screws
- Foundation:** Concrete - Steel base plate with four galvanized steel anchor bolts and galvanized steel hex nuts, washers and lock washers.



### Counterweight Box / Base Plate Detail



For 5" and 6"  
Diameter Poles



For 7", 8" and 9"  
Diameter poles

Counterbalance  
Weight Material  
for Box supplied  
by others.

### Custom order options:

- Finishes** Choose from fourteen standard or custom  
: powder paint colors or anodized finishes, or  
specify your own color.