

Nautical, Single or Double Mast

Our standard selection of nautical flagpoles are available in mounted heights from 25 ft. to 80 ft., with yardarm length ranging from 8 ft. to 18'-9", with a ground set foundation. For further assistance please refer to the Contact Us page for questions.

Nautical Standard Flagpoles, Ground Set:

- Material:** Alloy 6063-T6 aluminum tubing with uniform conical taper
- Finish:** Directional sanded satin ground or choose from six other powder coat paint or anodized finishes
- Finial:** Gold anodized aluminum ball with flush seam
- Truck:** Single or double revolving with stainless steel bearings. Eye hook mounted single pulleys on yard arm and/or gaff
- Halyard:** Four or Five #10 (5/16-dia.) braided polypropylene ropes each with two chrome plated bronze swivel snap hooks and covers
- Cleats:** Four or Five 9" cast aluminum
- Collar:** Spun aluminum flash collar finished to match pole
- Foundation:** Ground Set foundation - sleeve fabricated from 16-gauge galvanized corrugated steel tube with a 3/16-inch thick steel base plate and support plate, 3/4-inch diameter x 18 inches long ground (lightning) spike and steel centering wedges.

Select one of the following as a standard option:

- Mast:** Single or double mast

Custom order options:

- Foundations:** Shoe Base foundation - Cast aluminum shoe base with four galvanized steel anchor bolts and galvanized steel hex nuts, washers and lock washers.
- Finishes:** Choose from fourteen standard or custom powder paint colors or anodized finishes, or specify your own color.
- Gaff:** Gaff assembly available (yardarm and/or gaff assembly shipped as separate section)


Counter-Balanced

Our standard selections of counter balanced flagpoles are available in mounted heights from 30 ft. to 50 ft. with a concrete foundation. If you require options other than a standard flagpole, contact Mason-Hall [here](#).


Counter Balanced Standard Flagpoles, Tilting:

- Material:** Alloy 6063-T6 aluminum tubing with uniform conical taper. Counterweight box, base plate and support channels are made of steel
- Finish:** Directional sanded satin ground. Counterweight box matches color of pole
- Finial:** Gold anodized aluminum ball with flush seam
- Truck:** Single or double metal sheave cast aluminum with stainless steel bearing
- Halyard:** One or two #10 (5/16-dia.) braided polypropylene rope each with two chrome plated bronze swivel snap hooks
- Cleats:** One or two 9 inch cast aluminum, each attached with two 5/16-inch stainless steel screws
- Foundation:** Concrete - Steel base plate with four galvanized steel anchor bolts and galvanized steel hex nuts, washers and lock washers.

Counterweight Box / Base Plate Detail



For 5" and 6"
Diameter Poles



For 7", 8" and 9"
Diameter poles

Counterbalance
Weight Material
for Box supplied
by others.

Custom order options:

Finishes: Choose from fourteen standard or custom powder paint colors or anodized finishes, or specify your own color.